
EB-815E



























EB-815E, Epson's first 4KE super-ultra-short-throw laser display designed for businesses, hybrid working and immersive spaces

The EB-815E can be placed just centimetres away from a wall to create bright 4KE images up to 160". It projects content in stunning clarity and offers a low cost, energy efficient large display solution with a convenient and quick set up.

EB-815E's super-ultra-short-throw lens allows discreet positioning close to the wall, enabling presenters free access without casting shadows.

With 5,000 lumens CLO and 3LCD technology, the EB-815E is bright and vibrant up-to 160", which enables content visibility from all angles and distances. The experience is immersive and it's extremely simple to use.

Versatile wired and wireless connectivity options, including Miracast™ screen mirroring, ensure effortless, multi-device content sharing.

Weighing only 12.3kg, it is highly portable, and the Epson Setting Assistant App makes setup quick and simple. The ideal display solution suitable for different room sizes, combined with flexible installation options.

The EB-815E supports multiple aspect ratios and multi-projector edge-blending for a low cost, seamless, energy efficient ultra-wide display, perfect for video conferencing.

Paired with Epson's Ambient Light Rejection Screen, the EB-815E's image quality could be mistaken for a video wall or LED display, but it is surprisingly affordable and consumes a fraction of the energy.

KEY FEATURES

- Scalable 4KE display for any room 80-160" UST display for unrestricted viewing (no shadows/reflections)
- Bright and energy efficient laser 5,000 lumens CLO with 3LCD technology for brighter colours
- Effortless connectivity options
 Auto-on, wired/wireless display with
 USB 2A output for smart sticks
- Simple to use and built to last Virtually maintenance free with 5-year, 12,000hr warranty
- LED/Video wall alternative
 Surprisingly affordable with low energy consumption
- Legal Statement

Complies with The UK Product Security and Telecommunications Infrastructure (Product Security) requirements. Epson will provide security updates for 7 years from purchase



PRODUCT SPECIFICATIONS

TECHNOLOGY

Projection System 3LCD Technology, RGB liquid crystal shutter

LCD Panel 0.62 inch with C2 Fine

IMAGE

Color Light Output 5,000 Lumen - 3,500 Lumen (economy) In accordance with IDMS15.4

White Light Output 5,000 Lumen - 3,500 Lumen (economy) In accordance with ISO 21118:2020

Resolution 1080p

High Definition 4K enhancement

Aspect Ratio 16:9

Contrast Ratio Over 5,000,000 : 1

Light source Laser

Laser Light source 20,000 hours Durability High, 30,000 hours Durability Eco

Colour Video Processing 10 Bits
2D Vertical Refresh Rate 192 Hz - 240 Hz
HDR support HDR10, HLG

OPTICAL

Throw Ratio 0.16 - 0.40:1
Zoom Digital, Factor: 1 - 1.35

Lens Optical

Screen Size 80 inches - 160 inches

Projection Lens F Number 1.8
Projection Lens Focal Length
Projection Lens Focus Manual
Offset 7:1

CONNECTIVITY

Interfaces USB 2.0-A (2x), USB 2.0 Type B (Service Only), RS-232C, Ethernet interface (100 Base-TX / 10

Base-T), Wireless LAN IEEE 802.11a/b/g/n/ac, HDMI in (2x), HDMI out, HDBaseT, Miracast

Epson iProjection App Ad-Hoc / Infrastructure

Network Protocol HTTPS, IPv4, IPv6, SNMP, ESC/VP.net, PJLink

ADVANCED FEATURES

Security Kensington lock, Control panel lock, Password lock, Padlock, Wireless LAN unit lock, Wireless

LAN security, Password protection

3D No

2D Colour Modes Dynamic, Natural, Cinema, Presentation, Blackboard, DICOM SIM

Other features 21:9 aspect ratio support, 4K enhancement, A/V mute, Arc Correction, Auto Power On, Auto

source search, Built-in speaker, CEC compatible, Customizable user logo, Daisy chain Multi-Projection, Digital zoom, Direct Power on/off, Document Camera Compatible, Edge Blending, Email notification, Fit to Screen, Home Screen, Horizontal and vertical keystone correction, Image Shift, JPEG Viewer, Long light source life, PC Free, Point correction, Power on button, Quick Corner, Schedule Function, Screen Mirroring, Source function, Split-Screen-Function, Ultra-wide display (16:6), Web Control, Web Remote, Wireless LAN capable, iProjection App Blackboard, Cinema, Dynamic, Natural, Presentation, DICOM SIM, Multi Projection

Video Color Modes Blackboard, Cinema, Dynamic, Natural, Presentation, DICOM SIM, Multi Projection
Projector control via: AMX, Extron, Crestron Integrated Partner, Extron IP Link, Extron XTP, AMX Device

Discovery, Control4 Simple Device Discovery Protocol

EB-815E

WHAT'S IN THE BOX

- Quick Start Guide
- Power cable
- Remote control incl. batteries



PRODUCT SPECIFICATIONS

EB-815E

GENERAL

Power consumption 290 Watt (Normal On-Mode), 192 Watt (Eco On-Mode), 380 Watt (Normal Peak-mode), 286

Watt (Eco Peak-Mode), 0.4 Watt (Energy saving standby)

Heat Dissipation 1,292 BTU/hour (max)
Supply Voltage AC 100 V - 240 V, 50 Hz - 60 Hz

Product dimensions 695 x 341 x 156 mm (Width x Depth x Height)

Product weight 12.5 kg

Noise Level Normal: 35 dB (A) - Economy: 26 dB (A)

Supported Temperature Storage -10° C - 60° C

Supported Humidity Operation 20% - 80%, Storage 10% - 90%

If the projector is suspended from a ceiling or wall mount and installed in an environment with heavy oil smoke or places where oils or chemicals are volatilized, places where a lot of smoke or bubbles are used for event staging, or where aroma oils are frequently burned, it can make certain parts of our products susceptible to a material degradation which over time could

break and cause the projector to drop from the ceiling.

If you are concerned about the environment in which your projector is installed, or if you have any other questions, please contact our support department and they can provide additional

assistance

Included Software Epson Creative Projection, EasyMP Multi PC Projection, Epson Projector Content Manager,

Epson Projector Management, Epson Setting Assistant

Options Air filter, Ceiling mount, Connection and control box, MB22 ceiling mount, Safety wire set,

Visualiser camera, WP System - ELPWP10, WP System - ELPWP20, Wall hanging bracket,

Wall mount, Wireless LAN unit, Wireless transmitter - ELPWT01

Room Type / Application 4K Streaming, Boardroom, Huddle space / Portable, Large Meeting Room / Auditorium,

Meeting room / Classroom, Signage / Retail, Visitor Attraction

Positioning Ceiling Mounted, Desktop, TV Cabinet, Wall Mounted

Colour Black

OTHER

Warranty 60 months Carry in or 12,000 h
Optional warranty extension available

Optional warranty extension available



OPTIONAL ACCESSORIES

- Laser TV 100" ALR Screen ELPSC35 V12H002AD0
- Laser TV 120" ALR Screen ELPSC36 V12H002AG0
- Wall Mount ELPMB87 EB-815E V12H006AZ0
- Adapter ELPAP11 Wireless LAN (5GHz) V12H005A01
- Air Filter ELPAF64 EH-LS800 V13H134AE0
- Ceiling Mount (White) ELPMB22 V12H003B22
- Ceiling Mount (Low profile) ELPMB30 V12H526040
- Ceiling Pipe (450mm) ELPFP13 V12H003P13
- Ceiling Pipe (700mm) ELPFP14 V12H003P14

LOGISTICS INFORMATION

sкu	V11HA99180
EAN code	8715946726540
Country of Origin	China
Layer	2 Units
Layer Block	2 Units

Wireless Presentation Systems

- Epson ELPWP10 Wireless Presentation System V12HA41040
- Epson ELPWP20 Wireless Presentation System V12HA42040

Visualizers

- ELPDC07
 - V12H759040
- ELPDC13V12H757040DA
- ELPDC21

V12H758040DA

For more information please contact:

Home users: 0343 90 37766
Business users*: 0871 42 37766
Republic of Ireland: 01 436 7742
Or visit us at https://www.epson.co.uk/contactus
* 10p per minute plus network extras.

Web: www.epson.co.uk www.epson.ie



EB-815E