

imagePROGRAF TC-21 AFFORDABLE QUALITY IN A COMPACT DESIGN

A compact, affordable and sustainable desktop 24" large format printer delivers professional quality in small spaces. It is easy to use, perfect for home and small office in AEC segment, retail shop, hospitality, school, regardless of budget and space constraints.

BENEFITS

Affordable high quality

Variety of prints can be created with different sizes of cut sheets. Time is saved in trimming posters printed with minimised margins. High-quality pigment inks with advanced image processing, result in denser colours and sharper image¹. These lead to impactful prints without compromise on quality.

Hybrid support

Make hybrid working seamless by switching easily between your home and office printers. The imagePROGRAF TC-21 shares software such as job submission tools (Direct Print Plus, Free Layout Plus, etc.) with your office-based imagePROGRAF 5-colour models (TZ, TX, TM).

• Easy to use

A shaftless roll holder and optimised roll setting procedure make it simple to set up, while the tiltable operation panel allows a better view of information across different heights. The builtin auto-sheet feeder allows printing between roll and cut sheet without intervention, enabling various applications by accepting different cut sheet sizes.

Green at heart

Meet your sustainability goals with an EPEAT Gold² rating for its energy efficiency, packaging free from expanded polystyrene (EPS), and usage of 40% recycled plastic. Recyclable 70ml plastic ink bottles reduce ink replacement frequency. Reduced operation noise level makes it ideal for quiet environment.

1. COMPARE TO PREDECESSOR - IMAGEPROGRAF TC-20 2. EPEAT Gold registered in the U.S.



TECHNICAL SPECIFICATIONS

imagePROGRAF TC-21

PRINTER TECHNOLOGY		Media Take-up roll unit	N/A
Printer Type	4 Colour 24"	Borderless Printing Width (Roll Only)	A4, A3, A2, A1, B4, B3, B2, 17", 18", 24" Top/Bottom: Fully borderless; Left/Right: Approx. 0.5mm margin
Print Technology	Canon Bubble jet on Demand 4 colours integrated type (4 chips per print head x 1 print head)	Maximum number of delivered prints	Stand Basket (SD-24) / Desktop Basket (BU-06): Standard position - 1 sheet
Print Resolution	2,400 x 1,200 dpi	POWER AND OPERATING	
Number of Nozzles	Total : 4352 nozzles BK: 1280 nozzles C, M, Y : 1024 nozzles each	REQUIREMENTS Power Supply	AC 100-240V (50-60Hz)
Line Accuracy	±0.1% or less User adjustments necessary. Printing environment and media must match those used for the adjustments.	Power Consumption	Operation: Approx. 28W Sleep mode: Approx. 2.3W Default setting for the time to enter the Sleep mode:
Nozzle Pitch	1,200 dpi x 2 lines		Approx. 5 minutes Power off: Approx. 0.07W
Ink Capacity	Bundled Starter Ink: 280ml (70mlx4 for BK, C, M, Y) Sales Ink: 70ml (BK, C, M, Y)	Operating Environment	Temperature: 15-30°C, Humidity: 10~80% RH (no dew condensation)
Ink Type	Pigment inks: 4 colour BK/C/M/Y	Acoustic Noise	Operation: Approx. 41.5 dB(A)
OS Compatability	32 Bit: Windows7, Windows 81, Windows 10 64 Bit: Windows 7, Windows 81, Windows 10, Windows 11, Windows Server 2008R2, 2012, 2012R2, 2016, 2019, 2022, 2025 Apple Macintosh: macOS 11.7.10~macOS 14.15	(Pressure / Power)	(Plain paper, Standard mode, Line Drawing / text mode) Standby: 35 dB(A) or less (Measured on ISO 7779 standard)
Printer Languages	N/A (no direct print supported)		Operation: Approx. 6.0 Bels (Plain paper, Standard mode, Line Drawing / text mode)
Others Supported Job Submission Protocol	Apple AirPrint, Mopria, Chrome OS	Regulations	(Measured on ISO 7779 standard) CE mark, UKCA mark
Standard Interfaces	USB A Port: N/A	Environment Certificates	CB certfication, EPEAT GOLD ²
	USB B Port: Hi-Speed USB Ethernet: IEEE802.3u(100BASE-TX) / IEEE802.3(10BASE-T)	DIMENSIONS AND WEIGHT	
	Wireless LAN': IEEE802.11n/IEEE802.11g/IEEE802.11b/IEEE802.11a/ IEEE802.11ac	Physical Dimensions and	W x D x H Main Unit
MEMORY		Weight	968 x 533 x 245 mm (ASF closed, operation panel not tilted) 968 x 533 x 245 mm (ASF closed, operation panel tilted)
Standard memory	IGB Expansion slot: No		968 x 513 x 325 mm (ASF opened, operation panel titled) 32 kg (exclude ink bottle, include print head)
Hard Drive	N/A		Main Unit + Desktop Basket (BU-06)
PRINT SPEED			968 x 595 x 965* mm (ASF closed, operation panel not tilted, basket closed) 968 x 845 x 1115* mm
CAD Drawing:	Plain paper (Al, B&W): 0:30 (Standard)		(ASF opened, operation panel tilted, basket opened) 33 kg (exclude ink bottle, include print head) "Height above which cloth does not touch the floor when opening the
	Plain Paper (Al, Colour): 1:00 (Standard)		desktop basket.
Poster	Plain Paper (A1) 1:01 (Draft) 1:51 (Standard)		Main Unit + Stand + Basket (SD-24) 968 × 720 × 874 mm (ASF closed, operation panel not tilted, basket closed)
	Coated Paper (A1) 2:42 (Draft)		968 × 868 × 1024 mm (ASF opened, operation panel tilted, basket opened) 43 kg (exclude ink bottle, include print head)
MEDIA HANDLING	4.23 (Standard)	Packaged Dimensions and Weight	Printer (Main unit): 1120 x 726 x 406 mm, 45kg Desktop Basket (BU-06): 798 x 301 x 111 mm, 2.0kg Stand + Basket (SD-24): 1058 x 826 x 270 mm, 20kg
Media Feed and Output	Roll Paper: One Roll, Front-loading, Front Output Cut Sheet: Auto sheet feeder, Face-up, Front side	WHAT'S INCLUDED	Stand + Basket (30-24). 1030 x 020 x 270 mm, 20kg
Media Width	Roll paper : A3, A2, A2+, A1, B2, B3, 18", 24", 17" Cut sheet: A3, A4, A5, A6, B4, B5, B6, C4, Ledger, Letter, Legal, Foolscap, Executive, ARCH A, Photo (10"x12", 10"x15", 8"X10", 7"X10", 5"x7", 4"x6"(KG), 2L, L), Envelope (Com 10, DL, C5, Monarch), B-Oficio, M-Oficio, user-defined size (width: 89 mm - 297 mm, length: 127mm - 1200 mm)	What's in the Box? Software Included	Printer, 1 Print head, Power Cable, 1 Set of starter ink tanks, Installation Guide, Safety and Environmental Information, LFP Eur Address Sheet, Notice for PosterArtist WEB US/EU, Flange protective materials sheet Software available as Download from Web
Media Thickness	Roll/Cut : 0.08mm - 0.28mm	OPTIONS	
Minimum Printable Length	Roll paper: 203.2mm Cut sheet: 127mm	Optional Items	Desktop Basket: BU-06 Printer Stand + Basket: SD-24
Maximum Printable Length	Roll paper: 4m Cut sheet: 1200mm		
Maximum Media Roll Diameter	110mm	User Replaceable Items	Ink Tank: PFI-050 (70ml) Print Head: PF-08 Maintenance Cartridge: MC-32
Media Core Size	Internal diameter of roll core: 2"		
Margins Recommended area	Roll paper: Top: 5mm, Bottom: 5mm, Side: 5mm (some photo mode: Top: 30mm, Bottom: 30mm) Cut sheet: Top: 5mm, Bottom: 5mm, Side: 5mm	FOOTNOTE	
Margins Printable area	Roll paper: Top: 5mm, Bottom: 5mm, Side: 5mm (some photo mode: Top: 30mm, Bottom: 30mm)	 Please refer to user manual how to activate/deactivate the wireless LAN EPEAT Gold registered in the U.S. 	
	Roll paper (minimal margin print): Top: 0mm, Bottom: 0mm, Side: Approx. 0.5mm	DISCLAIMER	
Media Feed Capacity	Cut sheet: Top: 5mm, Bottom: 5mm, Side: 5mm Roll Paper: One roll	the specifications of the product have be	reproduction. All data is based on Canon's standard testing methods. This leaflet and een developed prior to the date of product launch. Final specifications are subject
	Cut Sheet: A4, Letter: 100 sheets (plain paper) A3, B4, Ledger, Legal, 10" x 12", 10" x 15": 50 sheets (plain paper) FS, Foolscap, ARCH A, C4, B-OFICIO, M-OFICIO: 10 sheets (plain paper) Others: 1 sheet	to change without notice. TM and "All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries. Canon recommends you use Canon Media for the best results. Please check media (paper) compatibility list to see which variety of paper/media is recommended.	

FINE Full-photolithography Inkjet Nozzle Engineering

Canon





Canon Inc. Canon.com

Canon Europe canon-europe.com

English Edition © Canon Europa N.V. 2025